

ThinkVision P32u-10 MONITOR

EXTREME COLOR, EXTREME FAST.



THE 32" WIDE COLOR GAMUT DISPLAY

Implementing the best-in-class display with latest technology, the 32" Lenovo™ ThinkVision® P32u display brings professional-grade color and innovative Thunderbolt™ 3.0 connector to your desktop. With Ultra-HD resolution, >99% AdobeRGB color gamut and Thunderbolt™ 3.0 technology, it delivers stunning visual experience and high productivity.

WHY YOU SHOULD BUY THE LENOVO THINKVISION P32u-10 MONITOR



Superb display

- 32" 4K Near Edgeless display
- Multi-color space (AdobeRGB, sRGB, DCI-P3, BT.709, BT.2020)
- Pre-calibrated color accuracy delta E<2



New user experiences

- Leading innovative Thunderbolt™ 3.0 (Titan Ridge)
- Compatible with USB 3.1 Type-C™
- Fast 40G/s data transition with 45 W power charging
- Dual 4K daisy chain support by Thunderbolt™



Enhanced productivity

- Easy multi-tasking by PIP & PBP
- KVM enables 1 key switch between dual hosts
- Dedicated software for color and display management

THE LENOVO THINKVISION P32u-10 MONITOR IS BEST SUITED FOR

1

Enterprises or small and medium businesses who want a high-performance professional display.

2

Advanced users who need a color-critical display for work.

3

Anyone who wants to implement the latest technology for versatile work with productivity.



ThinkVision P32u-10 MONITOR



SPECIFICATIONS

DISPLAY		ENVIRONMENTAL	
Panel Size	32"	Temperature	
Panel Type	In-Plane Switching	Operating	0°C – 40°C
Backlight	WLED	Non-Operating	-20°C – 60°C
Resolution	3840 x 2160	Humidity	
Aspect Ratio	16:9	Operating	8% – 80%
Anti-Glare	Yes	Non-Operating	5% – 95%
Screen Dimensions (W x H) (mm)	708.48 (H) x 398.52 (V)	Altitude	
Maximum Brightness (Typical)	300 cd/m ²	Operating	0 ft – 5000 ft
Viewing Angle (H/V at CR 10:1)	178°/178°	Non-Operating	0 ft – 40,000 ft
Contrast Ratio (Typical)	1000:1	Arsenic-Free Glass	Yes
Dynamic Contrast Ratio	3M:1	PVC-Free	Yes
Pixel Pitch (W x H) (mm)	0.1845 (H) x 0.1845 (V)	Mercury-Free	Yes
Dot/Pixel Per Inch (DP/PPI)	137	PCC % of Plastic Resins	85% with >25 g Plastic Parts
Color Gamut (1931)	99.5% AdobeRGB		
Response Time (Typical)	6 ms		
POWER CONSUMPTION		DIMENSIONS (W x D x H)	
Typical	70 W	Size Packed	
Maximum	200 W	(mm)	844 x 228 x 528
Sleep-Mode	≤0.5 W	(inches)	33.23" x 8.98" x 20.79"
Switch Off-Mode	≤0.5 W	Size Unpacked with Stand	
Power Supply	External	Lowest Position	
Power Voltage	90 VAC – 264 VAC	(mm)	726.7 x 350 x 497.8
Voltage Dynamic Frequency	47 Hz – 63 Hz	(inches)	28.61" x 13.78" x 19.6"
		Highest Position	
		(mm)	726.7 x 350 x 606.8
		(inches)	28.61" x 13.78" x 23.89"
		Size Unpacked without Stand	
		(Monitor Head Only)	
		(mm)	726.7 x 63.3 x 431.5
		(inches)	28.61" x 2.49" x 16.99"
		Distance from Table to Panel	
		Lowest Pixel at Bottom of Screen	
		(mm / inches)	90.9 / 3.58"
		Highest Pixel at Top of Screen	
		(mm / inches)	489.4 / 19.27"
		Stand Base Footprint Area	
		(mm / inches)	350 x 350 / 13.78" x 13.78"
		Weight	
		Packed	Starting at 29.32 lbs (13.3 kg)
		Unpacked	Starting at 22.05 lbs (10 kg)
		Monitor Head Only	Starting at 15.21 lbs (6.9 kg)
SIGNAL INPUT		COMPLIANCE	
Video Input Signals	2 x HDMI™ 2.0 + DisplayPort™ 1.2 + Thunderbolt™ 3.0-In + Thunderbolt™ 3.0-Out	EPEAT™	Gold
Video Cables Supplied	HDMI™, DisplayPort™, Thunderbolt™ 3.0	ENERGY STAR® Rating	7.0
Video Cable Length	2 m for Thunderbolt™, 1.8 m for HDMI™ and DisplayPort™	TCO	TCO 7.0 / TCO Edge 2.0
USB Hub	Yes (4 x Downstream, 1 x BC)	Windows Certification	Windows 7 / Windows 10
USB Cable Supplied	Yes (USB Type-A to Type-B)	China Energy Efficiency Standard	Tier 2
Audio-Out	Yes (3.5 mm)		
SIGNAL INTERFACE / PERFORMANCE		WARRANTY AND AVAILABILITY	
Horizontal Frequency	30 kHz – 160 kHz	Warranty	3 Years
Vertical Frequency	23 Hz – 80 Hz	Geography Availability	WW
Native Resolution	3840 x 2160		
Maximum Pixel Clock Speed / Bandwidth	HDMI™ : 600 MHz Display Port™: 5.4 Gbps Thunderbolt™: 10 Gbps		
Preset / User	28 / 20		
OSD Buttons	5 Buttons		
OSD Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian		
MECHANICAL			
Tilt Angle (Front / Back)	-5° / 22°		
Swivel Angle (Left / Right)	45° / 45°		
Lift (mm)	110		
(CW / CCW)	90° / 90°		
VESA® Mount (mm)	100 x 100		
Kensington® Lock Slot	Yes		
Cable Management	Yes		
Bezel Color	Raven Black		
Bezel Width			
Top (mm / inches)	2 / 0.08"		
Bottom (mm / inches)	23.8 / 0.94"		
Sides (mm / inches)	2 / 0.08"		



WWW.LENOVO.COM

Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic or typographic errors. All images are for illustration purposes only. For full Lenovo product, service and warranty specifications visit www.lenovo.com. Lenovo makes no representations or warranties regarding third party products or services. **Trademarks:** The following are trademarks or registered trademarks of Lenovo: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkStation, ThinkServer, ThinkVantage and ThinkVision. Microsoft, Windows and Vista are registered trademarks of Microsoft Corporation. Ultrabook, Celeron, Celeron Inside, Core Inside, Intel, Intel Logo, Intel Atom, Intel Atom Inside, Intel Core, Intel Inside, Intel Inside Logo, Intel vPro, Itanium, Itanium Inside, Pentium, Pentium Inside, vPro Inside, Xeon, Xeon Phi, and Xeon Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product and service names may be trademarks or service marks of others. Battery life (and recharge times) will vary based on many factors including system settings and usage. Visit www.lenovo.com/lenovo/us/en/safecomp/ periodically for the latest information on safe and effective computing. ©2017 Lenovo. All rights reserved.